

TEK CABLING , OUTPUTS C and D accessible

CCD Pin	flanged 20-41	TEK 1024 Function	mixed D con
49,23	H	V2u	8
51,21	g	V2l	8
50,22	P	V3	9
48,24	K	V1u	17
52,20	k	V1l	17
47,25	M	TGu	16
53,19	i	TGl	3
38	G	S1a	14
34	R	S1b	14
6	j	S1c	5
10	b	S1d	5
37	J	S2a	14
35	N	S2b	14
7	h	S2c	6
9	d	S2d	6
36	L	S3ab	14
8	f	S3cd	7
46	F	SWa	14
26	S	SWb	14
54	n	SWc	1
18	e	SWd	1
40	E	PhiRa	14
32	T	PhiRb	14
4	p	PhiRc	4
12	Z	PhiRd	4
42,30,14,2	Y	SUB	12
55,45,27,17	D	GND	12
39,33,11,5	m	LG	2
41	C	RDa	15
31	V	RDb	15
3	r	RDc	15
13	X	RDd	15
44	B	ODa	15
43	A	OSa	15
28	U	ODb	15
29	W	OSb	15
56	q	ODc	11
1	s	OSc	A2
16	c	ODd	11
15	a	OSd	A3

10 <- Connect to overall shields